

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 68 E., MDM, NEVADA

CHAINS	
	WP S 28 S 27 1987 This corner is located on a rocky spur, projecting W. 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T13N R68E $\frac{1}{4}$ S 28 S 27 1987 This corner is located on a spur, projecting WSW. 57.10 Ravine, drains W.
	80.00 Point for the cor. of secs. 27, 28, 33 and 34. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T13N R68E S 28 S 27 S 33 S 34 1987 Land, mountainous. Soil, rocky. Undergrowth, ceanothus, wild rosebush and native grass. Timber, pinon pine, mountain mahogany and aspen.
	S. 0° 02' E., bet. secs. 33 and 34. Over mountainous land, covered with dense timber and medium undergrowth.
	15.13 Point selected for the witness point bet. secs. 33 and 34. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	WP S 33 S 34 1987 This corner is located on a ridge, bearing E. and W.
	37.80 Creek in Williams Canyon, 10 lks. wide, 3 ft. deep, course W.
	40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.