

147

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 33 N., R. 54 E., MDM, NEVADA

CHAINS	
	<p>The cor. of Tps. 33 N., Rs. 54 and 55 E., monumented with a volcanic stone, 36X18X12 ins., loosely set in a mound of stone, plainly mkd. with 6 notches on the N. and W. edges.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;"> T33N R54E R55E S 36 S 31 ———— S T T32N R54E </p> <p style="text-align: center;">1987</p> <p>Corner is located 9 lks. S. of fence corner from which fences bear NNE. and W.</p> <p>S. 89° 44' W., along the S. bdy. of sec. 36.</p> <p>Over rolling land, through scattered sagebrush, rabbitbrush and native grass.</p>
11.30	Trail road on high ridge, bears N. and S.
40.21	<p>The S. ¼ sec. cor. of sec. 36, monumented with a volcanic stone, 12X8X6 ins., firmly set exposed 8 ins. above the ground, dimly mkd. ¼ on W. face, with a steel fence post, 5½ ft. long and a wooden post, 4 ins. square, 48 ins. long, firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T33N R54E ¼ S 36 ———— </p> <p style="text-align: center;">1987</p> <p>Deposit the original cornerstone and reset the steel fence post and wooden post alongside the stainless steel post.</p>
5.20	<p>S. 89° 45' W., beginning new measurement.</p> <p>Over rolling land.</p>
32.39	<p>Improved gravel road, bears NNW. and SSE.</p> <p>The closing corner of secs. 1 and 2, T. 32 N., R. 54 E., monumented with a stainless steel post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 32 N., R. 54 E., executed concurrently under this same Group.</p>