

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 45 N., R. 25 E., MDM, NEVADA

CHAINS		
	<p style="text-align: center;">T45N R25E R26E S 13 S 18 S 24 S 19</p> <p style="text-align: center;">1988</p> <p>Reset the iron pipe and set a steel fence post, 5½ ft. long and a carsonite post, 5 ft. long, alongside the stainless steel post.</p>	
	<p>N. 2° 53' W., bet. secs. 13 and 18.</p> <p>Over nearly level meadowland.</p>	
21.155	<p>Point for the S 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 13 S 18</p> <p style="text-align: center;">1988</p>	
26.00	Improved gravel road, bears NNE. and SSW.	
27.10	Improved gravel road, bears NNE. and SSW.	
36.00	Trail road, bears WNW. and ESE.	
42.31	<p>The ¼ sec. cor. of secs. 13 and 18, monumented with a basalt stone, 12X10X10 ins., firmly set 6 ins. in the ground with a rebar 5/8 in. diam., 18 ins. long, firmly set alongside, with a mound of stone W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T45N R25E R26E ¼ S 13 S 18</p> <p style="text-align: center;">1988</p> <p>Deposit the original cornerstone, rebar and set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>	
	<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES T. 45 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor G. W. Garside in 1879.</p>	