

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
TOWNSHIP 30 SOUTH, RANGE 64 EAST, MDM, NEVADA

CHAINS	
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.
54.00	Trail road, bears ENE. and WSW.
80.80	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron pin, 1 in. diam., firmly set showing 4 ins. above ground in a small mound of stone, with brass cap, 2 ins. diam., mkd. 1986 T30S R64E S31 S32 S6 S5 T31S RLS 2002, as recorded in Clark County, Record of Survey No. 623. This point is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30S R64E S 31 S 32 S 6 S 5 T31S</p> <p>1989</p> </div> <p>Deposit the RLS iron pin inside the stainless steel post and set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>From this corner, a rebar, ¾ in. diam., firmly set showing 8 ins. above ground, with brass tag mkd. RLS 2050, bears S. 31° 53' E., 0.29 chs. dist., This point is recorded in Clark County, Record of Survey No. 557. This point was not based on the best available evidence and therefore was not utilized in the course of this resurvey.</p>
	<p>N. 89° 43' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land, covered with creosote, greasewood and scattered cacti.</p>
19.23	Rebar, 5/8 in. diam., firmly set in ground, with plastic cap mkd. RLS 2002, in a fence bearing N. 11° 03' W. and S. 11° 03' E.
22.34	U.S. Highway No. 95, bears N. 11° 03' W. and S. 11° 03' E.
25.30	Underground gas pipeline, parallels U.S. Highway No. 95.
25.55	Fence line, bears N. 11° 03' W. and S. 11° 03' E.
35.10	Wash, 50 lks. wide, 2 ft. deep, drains SW.
40.41	<p>The ¼ sec. cor. of secs. 6 and 31, monumented with an iron pin, 1 in. diam., firmly set showing 4 ins. above ground in small mound of stone, with brass cap, 2 ins. diam., mkd. ¼ S31 S6 1986 RLS 2002, with a limestone, 16X8X8 ins., plainly mkd. ¼ on N. face, mkd. by RLS 2002, as recorded in Clark County, Record of Survey No. 623. This point is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p>