

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 30 SOUTH, RANGE 64 EAST, MDM, NEVADA

CHAINS	<p>From this corner, an unrecorded local monument, monumented with a wooden post, 5 ins. square, firmly set showing 48 ins. above ground, with aluminum tag on top mkd. 1 6 31 36, bears N. 88° 54' W., 10.57 chs. dist. This point was not based on the best available evidence and therefore was not utilized in the course of this resurvey.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 30 S., R. 64 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor W. H. Myrick in 1883</p> <hr/> <p>The ¼ sec. cor. of secs. 3 and 34, monumented with a basalt stone, 6X5X4 ins., loosely set in a mound of earth, plainly mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>T29S R64E S 34 ¼ S 3 T30S</div> <p>1989</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. long, N. of corner.</p> <p>From this corner, U.S.C. &amp; G.S. triangulation station "IBEX," hereinbefore described, bears S. 80° 47' W., (mean bearing) 209.35 chs. dist.</p> <p>S. 89° 57' W., bet. secs. 3 and 34.</p> <p>Over gently rolling land, covered with creosote, greasewood and scattered cacti.</p> <tr><td>20.00</td><td>Piute Wash, 50 lks. wide, 2 ft. deep, drains SSW.</td></tr> <tr><td>31.80</td><td>Trail road, bears NNE. and SSW.</td></tr> <tr><td>40.34</td><td><p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p><p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p><div>T29S R64E S 33   S 34 S 4   S 3 T30S</div><p>1989</p></td></tr>	20.00	Piute Wash, 50 lks. wide, 2 ft. deep, drains SSW.	31.80	Trail road, bears NNE. and SSW.	40.34	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>T29S R64E S 33   S 34 S 4   S 3 T30S</div> <p>1989</p>
20.00	Piute Wash, 50 lks. wide, 2 ft. deep, drains SSW.						
31.80	Trail road, bears NNE. and SSW.						
40.34	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>T29S R64E S 33   S 34 S 4   S 3 T30S</div> <p>1989</p>						