DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, TOWNSHIP 30 SOUTH, RANGE 64 EAST, MDM, NEVADA

	TOWNSHIP 30 SOUTH, RANGE 64 EAST, MDM, NEVADA
17.50	Fence, bears SSW. and NNE.
25.90	Trail road, bears SE. and NW.
40.34	Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29S R64E
	1989
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
 80.68	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29S R64E S 31 S 32 S 6 S 5 T30S
	1989
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
	From this corner, an unrecorded local monument, monumented with a 4X6 in. wooden post, firmly set showing 4 ft. above ground, no marks visible, bears S. 21°40' W., 1.89 chs. dist. This point was not based on the best available evidence and therefore was not utilized in the course of this resurvey.
	S. 89° 57' W., bet. secs. 6 and 31.
	Over gently rolling land, covered with creosote, greasewood and scattered cacti.
14.80	Power line, bears S. 21¾° E. and N. 21¾° W.
17.00	Trail road, parallels powerline.
40.34	The ¼ sec. cor. of secs. 6 and 31, monumented with a wooden post, 3 ins. square, 3 ft. long, with illegible scribe marks visible, loosely set in a mound of earth.
	At the corner point