

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 42 N., R. 60 E., MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 42 N., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA
	<p>Reestablishment of the Survey Executed by E. B. Monroe and E. C. McClellan, U.S. Deputy Surveyors, in 1881.</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 30' E., bet. secs. 35 and 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>
15.40	Ravine, drains W.
31.00	Ravine, drains SSW.
39.91	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T42N R60E <math>\frac{1}{4}</math> S 35 S 36</p> <p style="text-align: center;">1987</p>
79.82	<p>Set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p> <p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T42N R60E S 26 S 25 <u>S 35 S 36</u></p> <p style="text-align: center;">1987</p> <p>Set a steel fence post, 5<math>\frac{1}{2}</math> ft. long, alongside the stainless steel post.</p> <p>From this corner, a U.S.G.S. Bench Mark, monumented with a standard brass tablet set in the top of a concrete cylinder, 6 ins. diam., flush with the surface of the ground, stamped ELEV. 6218 FT. 112 DOR RESET 1968, bears S. 85° 53' W., 13.57 chs. dist.</p>