

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 55 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 55 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
M. F. Reilly and T. A. Magee, U.S. Deputy Surveyors,
in 1881

The standard cor. of secs. 34 and 35, monumented with
an embedded mound of stone. No wooden post found.
This mound of stone correlates well with other existing
original corners and is accepted as the best available
evidence of the position of the original corner, from
which the only remaining original bearing tree

A pinon pine, 8 ins. diam., bears N. 82° W., 95
lks. dist., mkd. SC BT. (Record: N. 35° W., 16
lks. dist.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins.
diam., 24 ins. in the ground, with brass cap mkd.

SC
T4S R55E
S 34 | S 35

1988

Set a steel fence post, 5½ ft. long, alongside the
stainless steel post.

N. 89° 33' W., along the S. bdy. of sec. 34.

Over mountainous land, through Brigham tea, cacti,
rabbitbrush, sagebrush, native grass and dense pinon
pine, mountain mahogany and juniper.

7.40 The cor. of secs. 5 and 6, T. 5 S., R. 55½ E.,
hereinafter described.

30.70 Spur, slopes N.

39.51 Point for the standard ¼ sec. cor. of sec. 34, at
proportionate distance; there is no remaining evidence
of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins.
diam., 8 ins. in the ground to solid rock and in a
mound of stone, 5 ft. base to top, with brass cap mkd.

SC
T4S R55E
¼ S 34

1988