

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 55 EAST, MDM, NEVADA

CHAINS	
	<p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>N. 89° 23' W., beginning new measurement.</p> <p>Over mountainous land.</p> <p>10.20 Ridge, bears SE. and NW.</p> <p>27.50 Trail road, bears SE. and NW.</p> <p>39.64 The standard cor. of secs. 32 and 33, monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the First Standard Parallel South, through a portion of R. 55 E., executed under Group No. 548.</p>
	<hr/> <p>SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 5 S., R. 55½ E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>The cor. of secs. 5 and 6, on the N. bdy. of the Tp., longitudinally at 160 chs. in departure from the closing cor. of secs. 1 and 2, T. 5 S., R. 55 E., and latitudinally on the First Standard Parallel South.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R55E S 34 S 6 S 5 T5S R55½E</p> <p>1988</p> </div> <p>S. 0° 01' W., bet. secs. 5 and 6.</p> <p>Over mountainous land.</p>
23.94	<p>Point for the 100 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R55½E 1/16 S 6 S 5 100</p> <p>1988</p> </div>
28.50	<p>Ridge, bears E. and W.</p>
43.94	<p>Point for the 80 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>