

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 5 SOUTH, RANGE 55½ EAST, MDM, NEVADA

CHAINS	
40.00	<p>EAST, bet. secs. 9 and 16, on a transit line describing the tangent.</p> <p>Over mountainous land.</p> <p>Point for the ¼ sec. cor. of secs. 9 and 16, NORTH, 0.2 lks. from the tangent.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R55½E S 9 ¼ S 16</p> <p style="text-align: center;">1988</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
84.77	<p>Intersect the Ruby Valley Guide Meridian.</p> <p>Point for the closing cor. of secs. 9 and 16, NORTH, 0.9 lks. from the tangent.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R55½E R56E CC S 9   S 18 S 16  </p> <p style="text-align: center;">1988</p> <p>from this corner,</p> <p>The original ¼ sec. cor. of secs. 13 and 18, Tps. 5 S., Rs. 55 and 56 E., monumented with a mound of stone, bears N. 1° 43' W., 5.26 chs. dist. No marked stone found. This mound of stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner. This mound of stone now becomes an angle point bet. sec. 9, T. 5 S., R. 55½ E. and sec. 18, T. 5 S., R. 56 E.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">AP T5S R55½E R56E S 9   S 18</p> <p style="text-align: center;">1988</p> <p>From this angle point, U.S. Mineral Monument No. 5, hereinafter described, bears N. 10° 53' W., 125.19 chs. dist.</p>