

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 67 EAST, MDM, NEVADA

<p>CHAINS 74.40</p>	<p>Trail road, bears NW. and SE.</p>
<p>80.30</p>	<p>The standard cor. of Tps. 16 N., Rs. 66 and 67 E., monumented with the decayed remains of a wooden post, loosely set in a collar of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T16N R66E R67E <u>S 36 S 31</u></p> <p style="text-align: center;">1987</p> <p>Reset the decayed remains of the original wooden post and set a wooden post, 3 ins. diam., 5½ ft. long, alongside the stainless steel post.</p>
<p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 16 N., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the Survey Executed by E. B. Monroe and A. G. Bateman, U.S. Deputy Surveyors, in 1871, the Resurvey Executed by W. A. Pray, U.S. Deputy Surveyor, in 1909 and the Resurvey Executed by P. L. Inch, Associate Cadastral Engineer, in 1942.</p>	
<p>From the standard cor. of Tps. 16 N., Rs. 67 and 68 E., monumented with an iron post, 3 ins. diam., firmly set showing 12 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 15 N., R. 68 E., executed under Group No. 64.</p> <p>N. 0° 02' E., bet. secs. 31 and 36.</p> <p>Over mountainous land, covered with medium sagebrush, scattered juniper, pinon pine, Brigham tea and native grass.</p>	
<p>3.80</p>	<p>Trail road, bears ENE. and WSW.</p>
<p>30.60</p>	<p>Spur, slopes W.</p>
<p>39.79</p>	<p>The ¼ sec. cor. of secs. 31 and 36, monumented with a quartzite stone, 20X18X11 ins., plainly mkd. ¼ on W. face, firmly set 12 ins. in the ground, with a mound of stone to the W.</p> <p>At the corner point</p>