

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 17 N., R. 67 E., MDM, NEVADA

CHAINS		
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.	
	N. 89° 33' W., bet. secs. 5 and 32.	
	Over gently rolling land, covered with medium rabbitbrush, scattered sagebrush and native grass.	
18.40	Slough, dry, drains irregularly N.	
19.10	Fence corner from which fences bear N., S. and W.; enter nearly level pasture of native grass, along fence.	
40.39	Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	$\begin{array}{r} \text{T17N R67E} \\ \text{S } 32 \\ \frac{1}{4} \text{ S } 5 \\ \text{T16N} \end{array}$	
	1987	
	Set a steel fence post, 5½ ft. long, alongside the stainless steel post.	
	This corner is located 0.03 chs. S. of fence bearing E. and W.	
80.78	The cor. of secs. 5, 6, 31 and 32, determined latitudinally in a fence bearing E. and W. and longitudinally by extending a fence line S. to an intersection with the E. and W. fence line.	
	At the corner point	
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	$\begin{array}{r} \text{T17N R67E} \\ \text{S } 31 \text{ } \text{S } 32 \\ \text{S } 6 \text{ } \text{S } 5 \\ \text{T16N} \end{array}$	
	1987	
	N. 89° 34' W., bet. secs. 6 and 31.	
	Over nearly level land, through pasture of native grass, along fence.	
11.10	Fence corner from which fences bear SSW., E. and W.	
39.62	The ¼ sec. cor. of secs. 6 and 31, determined latitudinally in a fence bearing E. and W. and longitudinally by extending a fence line S. to an intersection with the E. and W. fence line.	