

284

DEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH RANGE 65 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH RANGE 65 EAST, MDM, NEVADA

Reestablishment of the Survey Executed by
R. H. Woods and W. H. Myrick, U.S. Deputy Surveyors,
in 1881.

The standard cor. of Tps. 16 S., Rs. 65 and 66 E.,
monumented with an unmarked sandstone, 20X10X5 ins.,
firmly set in a mound of stone. This unmarked
sandstone correlates well with other existing original
corners and is accepted as the best available evidence
of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

SC
T16S
R65E R66E
S 36|S 31

1986

Deposit the unmarked stone alongside the aluminum post
and rebuild the mound of stone, 3 ft. base, 2 ft. high,
N. of cor.

S. 86° 40.6' W., along the S. bdy. of sec. 36.

Over rolling mountainous land, covered with scattered
chaparral, creosote and cacti.

11.660 The N ¼ sec. cor. of sec. 7, T. 17 S., R. 66 E.,
monumented with an aluminum post, 2½ ins. diam., firmly
set in a mound of stone, with aluminum cap mkd. as
described in the field notes of the dependent resurvey
of T. 17 S., R. 66 E., executed concurrently under this
same Group.

34.00 Enter gently rolling land.

40.687 Point for the standard ¼ sec. cor. of sec. 36, at
proportionate distance; there is no remaining evidence
of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

SC
T16S R65E
¼ S 36

1986

Set a steel fence post, 5½ ft. long, alongside the
aluminum post.