

289

DEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH RANGE 65 EAST, MDM, NEVADA

CHAINS	<p>S. 88° 03.4' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>11.431 The closing cor. of secs. 8 and 9, T. 17 S., R. 65 E., monumented with an aluminum post, 2½ ins. diam., firmly set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 17 S., R. 65 E., executed concurrently under this same Group.</p> <p>40.478 The standard cor. of secs. 31 and 32, monumented with an unmarked sandstone, 16X7X5 ins., firmly set in an embedded mound of stone. This unmarked sandstone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SC T16S R65E S 31 S 32</p> <p style="text-align: center;">1986</p> <p>Deposit the unmarked stone and set a steel fence post, 5½ ft. long, alongside the aluminum post and rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.</p> <p>From this corner, U.S.C. & G.S. triangulation station "CRYSTAL," identical with the standard cor. of secs. 31 and 32, T. 16 S., R. 65 E., established in 1938, (now an amended monument), monumented with an iron post, 3 ins. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of T. 17 S., R. 65 E., bears N. 74° 24' E., 17.90 chs. dist., executed concurrently under this same Group.</p>	
	<p>S. 89° 28.4' W., along the S. bdy. of sec. 31.</p> <p>Over gently rolling land, covered with scattered chaparral, mesquite and cacti.</p>	
10.972	<p>The N ¼ sec. cor. of sec. 8, T. 17 S., R. 65 E., monumented with an aluminum post, 2½ ins. diam., firmly set showing 8 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 17 S., R. 65 E., executed concurrently under this same Group.</p>	
15.746	<p>Intersect Valley of Fire County Road right-of-way, on a curve, curving to the right with a radius of 35.158 chs. dist., through an angle of 9° 23' 50.7" and with a length of curve of 5.766 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>	