

291

DEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH RANGE 65 EAST, MDM, NEVADA

CHAINS

SC
T16S
R64E R65E
S 36|S 31

1986

Deposit the unmarked stone alongside the aluminum post.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 16 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
R. H. Woods and W. H. Myrick, U.S. Deputy Surveyors,
in 1881.

From the standard cor. of Tps. 16 S., Rs. 65 and 66 E.
N. 0° 46.4' E., bet. secs. 31 and 36.

Over rolling mountainous land, covered with scattered
chaparral, creosote and cacti.

6.531 Intersect the 1938 Independent Resurvey of the Fourth
Standard Parallel South, not monumented, at a point
from which

The standard corner of Tps. 16 S., Rs. 65 and 66
E., monumented with an iron post, 3 ins. diam.,
firmly set in a mound of stone, with brass cap
mkd. as described in the field notes of the
independent resurvey of the Fourth Standard
Parallel South, through Rs. 65 and 66 E., under
Group No. 237, bears N. 89° 38.9' E., 17.799 chs.
dist. Hereafter, this cor. will function as an
angle point. Add the marks "AP 1986" to the brass
cap.

The N $\frac{1}{4}$ sec. cor. of sec. 7, (amended monument),
monumented with an iron post, 2 $\frac{1}{2}$ ins. diam.,
firmly set in a mound of stone, with brass cap
mkd. as described in the field notes of the
dependent resurvey of a portion of the west
boundary of T. 17 S., R. 66 E., executed
concurrently under this same Group, bears S. 89°
38.9' W., 11.740 chs. dist.

37.30 Ridge, bears WNW. and ESE.

40.539 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, at
proportionate distance; there is no remaining evidence
of the original corner.

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T16S
R65E R66E
 $\frac{1}{4}$
S 36|S 31

1986