

295

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 16 S., R. 65 E., MDM, NEVADA

CHAINS

T16S
R65E R66E
S 1|S 6
S 12|S 7

1986

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.

N. 0° 46.4' E., bet. secs. 1 and 6.

Over rolling land, covered with scattered chaparral, creosote and cacti.

40.539

The ¼ sec. cor. of secs. 1 and 6, monumented with an unmarked sandstone, 19X9X5 ins., firmly set in a mound of stone. This unmarked sandstone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T16S
R65E R66E
¼
S 1|S 6

1986

Deposit the unmarked stone alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 50.3' W., beginning new measurement.

Over rolling land.

7.10

Wash, 60 lks. wide, 2 ft. deep, drains NW.

19.304

Point for the N 1/16 sec. cor. of secs. 1 and 6.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

N 1/16
S 1|S 6

1986

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.