## 296

## DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 16 S., R. 65 E., MDM, NEVADA

	T. 16 S., R. 65 E., MDM, NEVADA
CHAINS	
38.608	The cor. of Tps. 15 and 16 S., Rs. 65 and 66 E., monumented with an unmarked sandstone, firmly set in a mound of stone. This unmarked sandstone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T15S R65E R66E S 36 S 31 S 1 S 6 T16S
	1986
	Deposit the unmarked stone alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, U.S.C. & G.S. triangulation station "VICKEY," monumented with a standard brass tablet set in bedrock, with brass tablet mkd. VICKEY 1957, bears S. 54° 39' W., 42.92 chs. dist.
	DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 16 S., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by R. H. Woods, U.S. Deputy Surveyor, in 1881.
	From the standard cor. of Tps. 16 S., Rs. 64 and 65 E.
	N. 0° 00.3' W., bet. secs. 31 and 36.
	Over nearly level land, covered with scattered chaparral, creosote and cacti.
20.40	Trail road, bears WSW. and ENE.
40.338	Point for the ½ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with aluminum cap mkd.
	T16S R64E <sub>,</sub> R65E
	S 36 S 31
	1986