

427

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 17 S., R. 65 E., MDM, NEVADA

CHAINS

Point for the N $\frac{1}{4}$ sec. cor. of sec. 10 is at intersection with the Fourth Standard Parallel South and the N. and S. center line of sec. 10.

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T16S R65E

$\frac{1}{4}$ S 10
T17S R65E

1986

Set a steel fence post, 5 $\frac{1}{2}$ ft. long, alongside the aluminum post.

From this corner, the standard cor. of secs. 33 and 34, T. 16 S., R. 65 E., monumented with an aluminum post, 2 $\frac{1}{2}$ ins. diam., firmly set showing 5 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 16 S., R. 65 E., executed concurrently under this same Group, bears N. 89° 24.2' E., 10.147 chs. dist.

From this same corner, the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the independent resurvey of T. 17 S., R. 65 E., executed under Group No. 373, bears S. 0° 02.0' E.

From this same corner, the N $\frac{1}{4}$ sec. cor. of sec. 10, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the independent resurvey of T. 17 S., R. 65 E., executed under Group No. 373, bears N. 0° 02.0' W., 2.351 chs. dist. Hereafter, this cor. will function as an amended monument.

Add the marks "AM 1986" to the brass cap.

from which

The standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 16 S., R. 65 E., monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the independent resurvey of T. 16 S., R. 65 E., executed under Group No. 237, bears S. 89° 59.1' W., 11.823 chs. dist. Hereafter, this cor. will function as an amended monument.

Add the marks "AM 1986" to the brass cap.

From the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of T. 17 S., R. 65 E., executed under Group No. 373.