

DEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF RANGE 19 EAST,  
TOWNSHIP 16 NORTH, RANGE 19 EAST, MDM, NEVADA

CHAINS  
79.610

The standard cor. of secs. 32 and 33, monumented with an iron pipe, 1½ ins. diam., 40 ins. long, projecting 10 ins. above a well embedded mound of stone, 3 ft. diam., found remnants of charred post directly adjacent to pipe, 5 ins. below the ground surface, from which the remains of the original bearing trees

A fir stump, 28 ins. diam., bears N. 55° 45' E., 169 lks. dist., with chaining notch and partial scribing visible. (Record, N. 56° 30' E., 168 lks.)

A burnt pine stump hole, 28 in. diam. bark ring, bears S. 59° 15' E., 57½ lks. dist. (Record, S. 60° E., 56 lks.)

A burnt fir stump hole, 28 in. diam. depression, bears S. 8° 00' W., 56 lks. dist. (Record, S. 7° W.)

A burnt fir stump hole, 36 in. diam. depression, bears N. 22° 00' W., 123 ½ lks. dist. (Record, N. 16° W., 127 lks.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

SC  
T16N R19E  
S 32 | S 33

1985

from which

A red fir, 12 ins. diam., bears N. 24° 15' E., 25 lks. dist., mkd. T16N R19E S33 SC BT.

A red fir, 20 ins. diam., bears N. 74° 15' W., 54 lks. dist., mkd. T16N R19E S32 SC BT.

Deposit iron pipe, horizontally, on S. side of stainless steel post.

Cor. is located on gentle W. slope.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 16 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA