

DEPENDENT RESURVEY OF THE
SIXTH STANDARD PARALLEL NORTH, THROUGH R. 55 E.,
MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE
SIXTH STANDARD PARALLEL NORTH, THROUGH R. 55 E.,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
C. C. Tracy, U.S. Deputy Surveyor,
in 1868
and the Survey and Resurvey Executed by
H. B. Maxson, U.S. Deputy Surveyor,
in 1896.

The standard cor. of Tps. 30 and 31 N., Rs. 55 and 56
E., monumented with the remains of a willow post, 1 in.
diam., 12 ins. long, lying loose on the ground, and a
wooden hub with metal tag, 12 ins. long, mkd. PUTR,
firmly set alongside.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins.
diam., 24 ins. in the ground, with brass cap mkd.

SC
T31N
R55E R56E
S 36 | S 31
S 1 | S 6
T30N

1987

Reset the remains of the original wooden post and
wooden hub and set a steel fence post, 5½ ft. long,
alongside the stainless steel post.

N. 89° 19' W., along the S. bdy. of sec. 36.

Over gently rolling land, through crested wheatgrass.

- 2.50 Fence, bears N. and S.
21.30 Fence, bears NNE. and SSW.
34.00 Huntington Creek, 20 lks. wide, 1 ft. deep, course NNW.
40.25 Point for the standard ¼ sec. cor. of sec. 36, at
proportionate distance; there is no remaining evidence
of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins.
diam., 24 ins. in the ground, with brass cap mkd.

SC
T31N R55E
¼ S 36

1987

Set a wooden post, 4 ins. diam., 5 ft. long, alongside
the stainless steel post.