

DEPENDENT RESURVEY OF THE  
SIXTH STANDARD PARALLEL NORTH, THROUGH R. 55 E.,  
MDM, NEVADA

CHAINS		
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T31N R55E <u>¼ S 32</u></p> <p style="text-align: center;">1987</p> <p>Reset the original wooden post and set a wooden fence post, 3 ins. diam., 4 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 18' W., beginning new measurement.</p> <p>Over mountainous land.</p>	
3.00	Ravine, drains NE.	
42.41	<p>The standard cor. of secs. 31 and 32, monumented with a volcanic stone, 24X15X13 ins., firmly set in a mound of stone, plainly mkd. with 5 notches on E. edge and 1 notch on W. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">SC T31N R55E <u>S 31   S 32</u></p> <p style="text-align: center;">1987</p> <p>Deposit the original cornerstone alongside the stainless steel post.</p> <p>Corner is located on top of high mountain.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 89° 30' W., along the S. bdy. of sec. 31.</p> <p>Over mountainous land, through scattered sagebrush, native grass and heavy juniper and pinon pine.</p>	
1.30	Ridge, bears NW. and SE.	
39.94	<p>Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T31N R55E <u>¼ S 31</u></p> <p style="text-align: center;">1987</p>	