TOWNSHIP 30 NORTH, RANGE 56 EAST, MDM, NEVADA

CHAINS

The geographic position for the closing corner of sections 3 and 4, is at latitude 40° 31' 10.00" N. and longitude 115° 39' 43.12" W., (NAD 27), as calculated from a direct tie to U.S.C. & G.S. triangulation station "SHEEP," located in section 28, T. 31 N., R. 56 E., and the geographic position for the southeast corner of section 34, is at latitude 40° 25' 54.5" N. and longitude 115° 38' 35.4" W., (NAD 27), as calculated along section lines from the previously named triangulation station.

The mean magnetic declination was found to be $17\frac{1}{2}^{\circ}$ E.

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH, THROUGH RANGE 56 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by C. C. Tracy, U.S. Deputy Surveyor, in 1868,

and the Portion of the Resurvey Executed by Executed by M. R. Collie, T. O. Nickerson and R. A. Pratt, Cadastral Surveyors, in 1974 to 1983.

From the standard cor. of Tps. 31 N., Rs. 56 and 57 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, through a portion of R. 56 E., executed under Group No. 506.

Add the marks 1987 to the brass cap.

N. 89° 37' W., along the S. bdy. of sec. 36.

- 2.70 The closing cor. of Tps. 30 N., Rs. 56 and 57 E., hereinafter described.
- 14.80 | Trail road, bears NW. and SE.
- Point for the standard ½ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC T31N R56E ⅓ S 36

1987

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.