

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH,
THROUGH RANGE 56 EAST, MDM, NEVADA

CHAINS
40.09

Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC
T31N R56E
 $\frac{1}{4}$ S 31

1987

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.

42.27

The N $\frac{1}{4}$ sec. cor. of sec. 6, T. 30 N., R. 56 E., hereinafter described.

80.18

The standard cor. of Tps. 30 and 31 N., Rs. 55 and 56 E., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 31 N., R. 55 E., executed concurrently under this same Group.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 30 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
A. J. Hatch, J. H. Eaton and J. C. Syles,
U.S. Deputy Surveyors,
in 1872.

The cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a wooden post, 3 ins. square, 26 ins. long, with illegible scribe marks visible, firmly set in a fence bearing E. and W.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30N R56E
S 34 | S 35
S 3 | S 2
T29N

1987

Reset the original wooden post and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.

S. $89^{\circ} 37'$ W., bet. secs. 3 and 34.