

177

DEPENDENT RESURVEY OF THE WEST BOUNDARY
(Ruby Valley Guide Meridian),
T. 30 N., R. 56 E., MDM, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R55E R56E ¼ S 1 S 6 1987</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>66.50 Trail road, bears E. and W.</p> <p>80.52 The standard cor. of Tps. 30 and 31 N., Rs. 55 and 56 E.</p>
<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 30 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of a Portion of the Survey Executed by A. J. Hatch, J. H. Eaton and J. C. Smyles, U.S. Deputy Surveyors, in 1872 and A Portion of the Survey Executed by A. J. Hatch, W. W. Skinner and C. S. Preble, U.S. Deputy Surveyors, in 1874.</p>	
40.95	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89° 25' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through scattered sagebrush, rabbit brush and native grass.</p> <p>Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R56E S 13 ¼ S 24 1987</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>81.90 The cor. of secs. 13, 14, 23 and 24, monumented with a granite stone, 12X10X4 ins., firmly set at the corner of a fence bearing N. and E., dimly mkd. with 3 notches on S. edge and 1 notch on E. edge (Record, charred post).</p>