

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 30 N., R. 56 E., MDM, NEVADA

CHAINS		
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R56E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">1987</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>	
40.18	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>S. 89° 28' W., bet. secs. 1 and 12.</p> <p>Over rolling land, through scattered sagebrush, rabbit brush and native grass.</p> <p>Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R56E S 1 ¼ S 12</p> <p style="text-align: center;">1987</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>	
80.36	<p>The cor. of secs. 1, 2, 11 and 12.</p>	
26.70	<p>N. 0° 11' E., bet. secs. 1 and 2.</p> <p>Over rolling reseeded land, through scattered sagebrush, rabbit brush and crested wheat grass.</p> <p>Willow Creek, 10 lks. wide, 2 ft. deep, course NW.</p>	
39.96	<p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	