## SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, TOWNSHIP 13 NORTH, RANGE 69 EAST, MDM, NEVADA

	TOWNSHIP TO NORTH, RANGE 09 EAST, MDM, NEVADA
CHAINS	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set exposed 10 ins. above ground, with brass cap mkd. as described in the field notes of the survey of T. 14 N., R. 69 E., executed under Group No. 95.
	From which the remains of the original bearing trees
	A dead and down pinon pine, 8 ins. diam., scribed T14N R69E S34 BT on an open blaze, the stump hole, bears N. 75¾° E., 110 lks. dist. (Record, N. 74½° E.)
	A dead and down pinon pine, 12 ins. diam., scribed T13N R69E S3 BT on an open blaze, the stump hole, bears S. $53\frac{1}{2}^{\circ}$ E., 55 lks. dist. (Record, S. 54° E., 47 lks. dist.)
	A pinon pine, 10 ins. diam., scribed T13N R69E S4 BT on a partially healed blaze, bears S. 14° W., 107 lks. dist. (Record, S. 12½° W., 110 lks. dist.)
	A dead and down pinon pine, 4 ins. diam., scribed T14N R69E S33 BT on an open blaze, the stump hole, bears N. 21°W., 136 lks. dist. (Record, N. 22½°W.)
	S. 0° 01' E., bet. secs. 3 and 4.
	Over mountainous land.
4.60	Small spur, slopes E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T13N R69E
	S 4 S 3
	1987
	Set a fiberglass post, 6 ft. long, alongside the stainless steel post.
43.30	Spur, slopes W.
55.70	Ridge, bears WNW. and ESE.
55.72	Point selected for a witness point bet. secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	WP S 4 S 3
	1987