DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, TOWNSHIP 12 NORTH, RANGE 70 EAST, MDM, NEVADA

TOWNSHIP 12 NORTH, RANGE 70 EAST, MDM, NEVADA	
CHAINS	Reestablishment of the Survey Executed by W. H. Good, U.S. Transitman in 1921
	The ½ sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the survey of T. 12 N., R. 70 E., executed under Group No. 71. Remark the brass cap to read as follows:
	T12N R70E
	S 17 S 16
	1921 1988
	N. 0° 03' W., bet. secs. 16 and 17.
	Over mountainous land, through scattered sagebrush, buckbrush, rosebush, native grass, juniper, pinon pine and cottonwood.
5.70	Spur, slopes E.
12.10	Ridge, bears E. and W.
34.04	Point selected for a witness point bet. secs. 16 and 17, on right bank of Snake Creek.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	WP S 17 S 16
	1988
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
34.20	Snake Creek, 10 1ks. wide, 1 ft. deep, course E.
39.94	The witness cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., lying loose on a mound of stone, with brass cap mkd. as described in the field notes of the survey of T. 12 N., R. 70 E., executed under Group No. 71, from which the remaining original bearing trees
	A pinon pine, 9 ins. diam., bears S. 76½° E., 221 lks. dist., mkd. WC T12N R70E S16 BT. (Record, S. 75½° E., 222 lks. dist.)
	A juniper, 8 ins. diam., bears S. $57\frac{1}{2}^{\circ}$ W., 241 lks. dist., mkd. WC T12N R70E S17 BT. (Record, S. $56\frac{3}{4}^{\circ}$ W., 243 lks. dist.)