

305

DEPENDENT RESURVEY OF
THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH RANGE 45 EAST, MDM, NEVADA

CHAINS	
	<p style="text-align: center;">SC T41N R45E <u>S 33 S 34</u></p> <p style="text-align: center;">1987</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.</p>
21.50	<p>N. 89° 51' W., along the S. bdy. of sec. 33.</p> <p>Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.</p>
40.75	<p>The N ¼ sec. cor. of sec. 6, T. 40 N., R. 45 E., hereinafter described.</p>
40.75	<p>Point for the standard ¼ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T41N R45E <u>¼ S 33</u></p> <p style="text-align: center;">1987</p>
57.66	<p>Raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p> <p>The closing cor. of Tps. 40 N., Rs. 44 and 45 E., hereinafter described.</p>
81.50	<p>Point for the standard cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">SC T41N R45E <u>S 32 S 33</u></p> <p style="text-align: center;">1987</p>
	<p>From this corner, a BLM project marker, monumented with an aluminum post, with cap mkd. "4789-RIMROCK," firmly set in the ground, bears N. 15° 16' W., 28.12 chs. dist.</p>
	<p>N. 89° 51' W., along the S. bdy. of sec. 32.</p> <p>Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.</p>