

306

DEPENDENT RESURVEY OF
THE EIGHTH STANDARD PARALLEL NORTH,
THROUGH RANGE 45 EAST, MDM, NEVADA

CHAINS 3.10	Spur, projects NE.
40.75	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R45E <u>$\frac{1}{4}$ S 32</u></p> <p style="text-align: center;">1987</p>
60.90	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Fence, bears ENE. and WSW.</p>
77.80	Trail road, bears NE. and SW.
81.50	<p>Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R45E <u>S 31 S 32</u></p> <p style="text-align: center;">1987</p>
40.20	<p>N. $89^{\circ} 51'$ W., along the S. bdy. of sec. 31.</p> <p>Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.</p> <p>Trail road, bears NNE. and SSW.</p>
40.75	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R45E <u>$\frac{1}{4}$ S 31</u></p> <p style="text-align: center;">1987</p> <p>Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.</p>