309

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 40 N., R. 45 E., MDM, NEVADA

	T. 40 N., R. 45 E., MDM, NEVADA
CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 40 N., R. 45 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by T. K. Stewart, U.S. Deputy Surveyor, in 1884.
	From the cor. of Tps. 39 and 40 N., Rs. 45 and 46 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 40 N., R. 46 E., executed under Group No. 464.
	S. 85° 17' W., bet. secs. 1 and 36.
	Over mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.
16.10	Ravine, drains NW.
29.80	Ridge, bears NW. and SE.
42.43	The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a limestone, 18X10X6 ins., dimly mkd. $\frac{1}{4}$ on N. face, firmly set in a mound of stone.
	At the corner point
1	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 13 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T40N R45E ¹ 4 <u>S 36</u> 5 T T39N
	1987
	Deposit the original cornerstone alongside the stainless steel post.
	S. 89° 38' W., beginning new measurement.
	Over rolling mountainous land.
21.20	Creek, 5 lks. wide, 6 ins. deep, course N.
39.91	The cor. of secs. 1, 2, 35 and 36, monumented with an unmarked stone, 18X10X10 ins., firmly set in a mound of stone, with a steel fence post set alongside the cornerstone. This unmarked stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.