

DEPENDENT RESURVEY OF
A PORTION OF THE SOUTH BOUNDARY,
T. 40 N., R. 45 E., MDM, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock and in a mound of stone, 2½ ft. base to top, with brass cap mkd.

T40N R45E
S 31 | S 32
S 6 | S 5
T39N

1987

S. 89° 52' W., bet. secs. 6 and 31.

Over mountainous land, covered with scattered sagebrush, rabbitbrush and native grass and aspen.

18.00 Deep ravine, drains NE.

30.10 Trail road, on Snowstorm Ridge, bears N. and S.

40.34 The ¼ sec. cor. of secs. 6 and 31, monumented with a trapstone, 18X9X3 ins., dimly mkd. ¼ on N. face, firmly set in an embedded mound of stone.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T40N R45E
¼ S 31
S 6
T39N

1987

Deposit the original cornerstone alongside the stainless steel post.

From this corner, U.S.C. & G.S. triangulation station "POLE," monumented with a standard brass tablet, firmly set in a rock outcrop with tablet mkd. "POLE 1934," bears S. 1° 46' W., 76.64 chs. dist.

DEPENDENT RESURVEY OF
A PORTION OF THE WEST BOUNDARY,
T. 40 N., R. 45 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
T. K. Stewart, U.S. Deputy Surveyor,
in 1884.

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a trapstone, 20X10X6 ins., dimly mkd. with 5 notches on N. edge and 1 notch on S. edge, firmly set in a mound of stone.

At the corner point