

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 45 E., MDM, NEVADA

CHAINS	
29.40	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 40 N., R. 46 E., executed under Group No. 464.</p> <p>S. 87° 18' W., bet. secs. 1 and 12.</p> <p>Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.</p>
40.69	<p>Castle Ridge, bears NNW. and SSE.</p> <p>Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R45E ¼ S 1 S 12 1987</p>
81.38	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>The cor. of secs. 1, 2, 11 and 12.</p>
45.94	<p>N. 9° 03' E., bet. secs. 1 and 2.</p> <p>Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.</p> <p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R45E ¼ S 1 S 2 S 1 1987</p>
82.90	<p>Top of hill.</p>
184.20	<p>Intersect the Eighth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground to solid rock and in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p>