

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 45 E., MDM, NEVADA

CHAINS 50.10	South Fork Little Humboldt River, 20 lks. wide, 1 ft. deep, course irregularly ENE.
65.90	South Fork Little Humboldt River, 20 lks. wide, 1 ft. deep, course irregularly NNW.
80.74	The cor. of secs. 2, 3, 10 and 11, monumented with an unmarked stone, 14X10X9 ins., firmly set in a mound of stone. This unmarked stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T40N R45E \\ S \ 3   S \ 2 \\ \hline S \ 10   S \ 11 \end{array}$
	1987
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	From the cor. of secs. 1, 2, 11 and 12.
	S. 89° 17' W., bet. secs. 2 and 11.
	Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.
1.80	Trail road, bears N. and S.
40.16	Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T40N R45E \\ \frac{1}{4} S \ 2 \\ \hline S \ 11 \end{array}$
	1987
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
65.90	Ridge, bears N. and S.
80.32	The cor. of secs. 2, 3, 10 and 11.
	N. 8° 16' E., bet. secs. 2 and 3.
	Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.