

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 40 N., R. 45 E., MDM, NEVADA

| CHAINS | |
|--------|--|
| 81.00 | <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with an unmarked stone, 18X9X8 ins., firmly set in a mound of stone. This unmarked stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T40N R45E S 4 S 3 S 9 S 10</p> <p>1987</p> </div> <p>Deposit the unmarked stone alongside the stainless steel post.</p> |
| 0.50 | <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89° 39' W., bet. secs. 3 and 10.</p> <p>Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.</p> |
| 11.00 | <p>South Fork Little Humboldt River, 20 lks. wide, 1 ft. deep, course N.</p> <p>Ravine, drains NNE.</p> |
| 40.59 | <p>Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T40N R45E ¼ S 3 S 10</p> <p>1988</p> </div> |
| 81.18 | <p>The cor. of secs. 3, 4, 9 and 10.</p> <p>N. 7° 54' E., bet. secs. 3 and 4.</p> |
| 45.62 | <p>Over rolling mountainous land, covered with scattered sagebrush, rabbitbrush and native grass.</p> <p>Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |