418

SURVEY OF TRACT NO. 40, TOWNSHIP 19 NORTH, RANGE 30 EAST, MDM, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T19N R30E S 10 | TR-40 | COR-3

1988

From this corner, the center $\frac{1}{4}$ sec. cor. of sec. 10, hereinbefore described, bears N. 2° 50′ 12″ W., 10.150 chs. dist.

From this same corner, the C-N-S 1/64 sec. cor. of sec. 10, hereinbefore described, bears N. $69\,^{\circ}$ $14\,^{\circ}$ $00\,^{\circ}$ W., 0.487 chs. dist.

From this same corner, the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented with a nail in the center of a metal tag, 1 in. diam., set flush with the surface of oil road, as described in the field notes of the dependent resurvey of T. 19 N., R. 30 E., executed under Group No. 568, bears S. 0° 38' 00" W., 29.724 chs. dist.

N. 89° 52' 00" E., along line 3-4 of Tract No. 40.

2.273 Point for Cor. No. 4, Tract No. 40.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T19N R30E TR-40| COR-4|S 10

1988

N. 0 $^{\circ}$ 06 $^{\circ}$ 00 $^{\circ}$ W., along line 4-1 of Tract No. 40.

0.176 Intersect the W_2 line of the E-W center line of the NW4 of the SE4 of sec. 10, at a point from which the C-N-S 1/64 sec. cor. of sec. 10, hereinbefore described, bears S. 89° 49' 24" W., 2.728 chs. dist.

1.515 | Cor. No. 1, Tract No. 40 and point of beginning.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF, T. 19 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Resurvey Executed by Cadastral Surveyors, N. R. Forsyth, R. E. Williams and D. E. Provost in 1978-78

The N 1/16 sec. cor. of secs. 19 and 20, monumented with a 60 D penny nail, set 6 ins. below the surface of a gravel road, as described in the field notes of the dependent resurvey of T. 19 N., R. 30 E., executed under Group No. 568. From which the reference marks set in 1978-79: