

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 14 NORTH, RANGE 26 EAST, MDM, NEVADA

<p>CHAINS</p>	<p style="text-align: center;"> T15N R26E S 36 T15N S T S 31 T14N R27E </p> <p style="text-align: center;">1989</p> <p>Deposit the original cornerstone and set a wooden post, 4 ins. square, 5 ft. long, alongside the stainless steel post.</p>
	<p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
<p>40.003</p>	<p style="text-align: center;">Reestablishment of the Survey Executed by H. E. Franks and J. S. Mullen, U.S. Deputy Surveyors in 1904.</p> <hr/> <p>The cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. monumented with a basalt stone, 14X8X6 ins., mkd. with 1 notch on S. edge and 5 notches on N. edge, firmly set 10 ins. in the ground, with a mound of stone W.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T14N R27E R28E S 25 S 30 S 36 S 31 </p> <p style="text-align: center;">1989</p> <p>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>N. 0° 00.7' W., bet. secs. 25 and 30.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>The ¼ sec. cor. of secs. 25 and 30, monumented with a basalt stone, 12X9X7 ins., mkd. ¼ on W. face, firmly set 8 ins. in the ground, with a mound of stone W.</p>