DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, TOWNSHIP 14 NORTH, RANGE 27 EAST, MDM, NEVADA

	TOWNSHIP 14 NORTH, RANGE 27 EAST, MDM, NEVADA
5.199	Southern Pacific Railroad right-of-way, bears S. 53° 20.0' E. and N. 53° 20.0' W.
7.735	Southern Pacific Railroad track, parallels right-of-way.
10.272	Southern Pacific Railroad right-of-way, bears S. 53° 20.0' E. and N. 53° 20.0' W.
27.80	Trail road, bears SSE. and NNW.
39.499	The ¼ sec. cor. of secs. 6 and 31, monumented with a redwood post, 4 ins. square, 36 ins. long, with illegible scribe marks visible, firmly set 27 ins. in the ground, with a basalt stone, 18X8X4 ins., mkd. ¼ on N. face, firmly set alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T15N R27E S 31 S 6 T14N
	1989
	Reset the original wooden post and deposit the marked stone alongside the stainless steel post.
	N. 89° 51.9' W., beginning new measurement.
	Over rolling land.
35.200	The closing cor. of Tps. 14 and 15 N., Rs. 27 E., monumented with a granite stone, 20X7X5 ins., mkd. with 6 grooves on N., S. and E. faces, with CC on E. face. Mark the stone AM for amended monument and bury.
35.356	Intersect the E. bdy. of sec. 1, T. 14 N., R. 26 E.
	Point for the closing cor. of Tps. 14 and 15 N., Rs. 27 E.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.