

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 15 NORTH, RANGE 27 EAST, MDM, NEVADA

CHAINS	<p>Set a wooden post, 4 ins. square, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with a redwood post, 3 ins. square, 36 ins. long, with illegible scribe marks visible, firmly set 24 ins. in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R27E S 29 $\frac{1}{4}$ S 32</p> <p style="text-align: center;">1989</p> <p>Reset the original wooden post and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.</p> <p>S. $89^{\circ} 54.2'$ W., bet. secs. 29 and 32.</p> <p>Over nearly level bottom land, through thick willows and greasewood.</p> <p>35.90 Left bank Walker River, bears N. and S.</p> <p>38.30 Right bank Walker River, bears N. and S.</p> <p>39.674 Point for the original witness cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner or the original bearing tree.</p> <p>POINT NOT MONUMENTED.</p> <p>39.853 The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>S. $89^{\circ} 57.1'$ W., bet. secs. 30 and 31.</p> <p>Over gently rolling land, through thick willows and greasewood.</p> <p>39.773 The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a redwood post, 4 ins. square, 36 ins. long, with illegible scribe marks visible, firmly set 24 ins. in the ground.</p>
--------	---