DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 19 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T18S R61E S 31 ¼ S 6 T19S 1990 Set a steel fence post, 5½ ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
80.598	The cor. of Tps. 18 and 19 S., Rs. 60 and 61 E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 19 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
R. H. Woods and W. H. Myrick, U.S. Deputy Surveyors
in 1882.

The cor. of secs. 19, 20, 29 and 30, monumented with a metal cap cemented in a concrete monument, 6 ins. diam., exposed 3 ins. above the ground, mkd. RE&RLS 290 S19 S20 S29 S30 T19S R61E. This cap correlates well with other existing original corners and is accepted as a careful and faithful perpetuation of the position of the original corner. Remark the cap to read as follows:

RE&RLS 290
BLM
S 19 | S 20
S 30 | S 29
T19S R61E

1990

From this corner, an unmarked brass cap, cemented in a concrete monument, 10 ins. diam., firmly set and exposed 18 ins. above the ground, bears N. 64° 41' W., 0.396 chs. dist.

From this same corner, U.S.C. & G.S. triangulation station "SNIPE", monumented with a standard brass tablet firmly set in concrete, mkd. SNIPE 1957, bears S. 84° 49.1' E., (mean bearing), 299.53 chs. dist.