

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 54 EAST,
T. 20 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this same corner, the standard cor. of Tps. 20 S., Rs. 53 and 54 E., monumented with an aluminum cap, set flush with Gamebird Road, mkd. VTN ENGR CO RLS 2050, identical with the U.S.C. & G.S. triangulation station "GLO 3A", bears S. 89° 46.9' W., (mean bearing), 81.546 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by T. Binge,
U.S. Deputy Surveyor in 1881.

From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp.

N. 0° 17.7' E., bet. secs. 32 and 33.

Over level land, along Earp Ave.

20.448

The S 1/16 sec. cor. of secs. 32 and 33, monumented with a brass cap, cemented in a concrete monument, 6 ins. diam., firmly set 2 ins. below the surface of the ground, mkd. VTN SE 1/16 S32S33 RLS 4046. This cap is accepted as a careful and faithful determination of the position of the corner. This monument meets the standards set by the Bureau and was not remonumented.

From this corner

A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 54° 50' E., 0.748 chs. dist., with brass cap mkd. S 1/16 S33 RM 49.4 FT 1990 and an arrow pointing to the true corner.

A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 44° 58' W., 0.629 chs. dist., with brass cap mkd. S 1/16 S32 RM 41.5 FT 1990 and an arrow pointing to the true corner.