

271

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 21 S., R. 54 E., MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 21 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA
	<p>Reestablishment of the Survey Executed by J. M. Brunt and W. H. Proctor, U.S. Deputy Surveyors, in 1881.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the resurvey of T. 22 S., R. 54 E., executed under California Group No. 250. Add the marks 1990 to the brass cap.</p>
	<p>N. 1° 19.4' W., bet. secs. 34 and 35.</p>
	<p>Over nearly level land, through scattered sagebrush, creosote and cacti.</p>
39.882	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21S R54E $\frac{1}{4}$ S 34 S 35 1990</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
79.50	<p>Wash, 20 lks. wide, 3 ft. deep, drains W.</p>
79.764	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a limestone, 15x9x9 ins., plainly mkd. with 1 notch on the S. edge, 2 notches on the E. edge and firmly set in a mound of stone, with a rebar, $\frac{5}{8}$ in. diam., 20 ins. long, firmly set alongside, exposed 8 ins. above the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>