281

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 21 S., R. 54 E., MDM, NEVADA

1. 21 S., R. 54 E., MUM, NEVADA	
CHAINS	T21S R54E S 21 \$\frac{1}{4}\$ \frac{5}{5}\frac{28}{28}\$
	1990
	From this corner, U.S.G.S. Bench Mark, monumented with a standard brass tablet, firmly set in concrete with brass tablet mkd. 2753 12RBO 1981, bears N. 55° 59' E., 1.011 chs. dist.
	From this same corner, a rebar, ½ in. diam., firmly set flush with the ground, with plastic cap mkd. RLS 5492, bears N. 73°02' E., 0.946 chs. dist.
41.30	Enter Turner Road, curving from NE. to W.
75.30	Power line, bears N. 82½° E. and S. 82½° W.
81.160	The cor. of secs. 20, 21, 28 and 29.
	SURVEY OF THE SUBDIVISION OF SECTION 28, T. 21 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the ½ sec. cor. of secs. 28 and 33.
:	N. 1° 28.9' W., on the N-S center line of sec. 28.
	Over nearly level land, through scattered sagebrush and creosote.
29.50	Trail road, bears NW. and SE.
40.291	Point for the center $\frac{1}{4}$ sec. cor. of sec. 28, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T21S R54E C¼ S 28
	1990
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.