

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 19 SOUTH, RANGE 55 EAST, MDM, NEVADA

CHAINS	
	<p>From the cor. of Tps. 18 and 19 S., Rs. 55 and 56 E., monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the resurvey of T. 19 S., R. 56 E., executed under Group No. 147, from which the bearing trees mkd. in 1933</p> <p>A bristlecone pine, 12 ins. diam., bears S. $88\frac{1}{4}^{\circ}$ E., 104 lks. dist., mkd. T18S R56E S31 BT on open blaze. (Record, N. $87\frac{1}{2}^{\circ}$ E., 103 lks.)</p> <p>A ponderosa pine, 24 ins. diam., bears S. 71° E., 170 lks. dist., mkd. T19S R56E S6 BT on partially healed blaze.</p> <p>A ponderosa pine, 15 ins. diam., bears S. $56\frac{1}{2}^{\circ}$ W., 185 lks. dist., mkd. T19S R55E S1 BT on partially healed blaze. (Record, S. $62\frac{3}{4}^{\circ}$ W.)</p> <p>This corner is located 50 lks. S. of ridge, bears E. and W., 0.50 chs. then SW.</p> <p>N. $89^{\circ} 25'$ W., bet. secs. 1 and 36.</p> <p>Over mountainous land, through pine, juniper and scattered mahogany; covered with sparse undergrowth.</p>
15.00	Spur, projects NW.
43.145	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T18S R55E</p> <p>S 36</p> <p>$\frac{1}{4}$ $\overline{\text{S T}}$</p> <p>T19S</p> <p>1988</p> </div> <p>from which</p> <p>A pinon pine, 18 ins. diam., bears N. 70° E., 22 lks. dist., mkd. $\frac{1}{4}$ S36 BT.</p> <p>A pinon pine, 19 ins. diam., bears S. $6\frac{1}{4}^{\circ}$ W., 67 lks. dist., mkd. $\frac{1}{4}$ S1 BT.</p>