

305

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 19 SOUTH, RANGE 55 EAST, MDM, NEVADA

CHAINS

Reestablishment of the Survey Executed by T. Binge,  
U.S. Deputy Surveyor, in 1881.

From the cor. of secs. 12 and 13, monumented with an iron post,  
2 ins. diam., firmly set in a mound of stone, with brass cap  
mkd. as described in the field notes of the resurvey of T. 19  
S., R. 56 E., executed under Group No. 147, from which the  
bearing trees mkd. in 1933

A ponderosa pine, 24 ins. diam., bears S.  $15\frac{1}{2}^{\circ}$  W., 146 lks.  
dist., mkd. T19S R55E S13 BT on partially healed blaze.

A ponderosa pine snag, 19 ins. diam., bears N.  $38\frac{1}{2}^{\circ}$  W., 65  
lks. dist., mkd. T19S R55E S12 BT on open blaze.

Remark the brass cap to read as follows:

T19S	T19S
S 12	S 7
S 13	R56E
R55E	

1989  
1933

This corner is located on ridge bearing ESE. and WNW.  
N.  $88^{\circ} 35'$  W., bet. secs. 12 and 13.

Over mountainous land, through pine, fir and mahogany; covered  
with sparse undergrowth.

10.00 Ridge, bears NW. and E.

42.63 Point for the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, at proportionate  
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins.  
in the ground to solid rock and in a mound of stone, 3 ft. base  
to top, with brass cap mkd.

T19S R55E
S 12
$\frac{1}{4}$ S 13

1989

from which