

313

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 19 SOUTH, RANGE 55 EAST, MDM, NEVADA

CHAINS	
	No suitable bearing trees available within limits.
	<hr/> <p style="text-align: center;">SURVEY OF THE SUBDIVISION OF SECTION 1, T. 19 S., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
	N. $0^{\circ} 24'$ E., on the N. and S. center line of sec. 1.
1.00	Top of ledge, edge bears E. and W.
14.10	Bladed road, bears SE. and NW.
19.285	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 1.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T19S R55E C S $\frac{1}{16}$ S 1 C</p> <p style="text-align: center;">1989</p>
20.00	Ridge, bears E. and W.
26.00	Bladed road, bears E. and W.
26.80	Ravine, drains W.
38.57	Point for the C $\frac{1}{4}$ sec. cor. of sec. 1, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T19S R55E C $\frac{1}{4}$ S 1</p> <p style="text-align: center;">1989</p>
58.30	Spur, projects WNW.