

429

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 19 SOUTH, RANGE 60 EAST, MDM, NEVADA

<p>CHAINS 79.986</p>	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 19 S., R. 60 E., executed under Group No. 357.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by R. H. Woods and W. H. Myrick, U.S. Deputy Surveyors in 1882.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a metal cap cemented in a concrete monument, 6 ins. diam., set flush with the ground, with metal cap mkd. as described in the field notes of the dependent resurvey of T. 19 S., R. 61 E., executed under Group No. 683.</p> <p>S. 87° 02.4' W., bet. secs. 24 and 25.</p> <p>Over nearly level land, through scattered shadscale and creosote brush.</p> <p>19.236 Point for the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $E \frac{1}{16} \frac{S \ 24}{S \ 25}$ <p>1990</p> </div> <p>From this corner, a rebar, 5/8 in. diam., firmly set flush with the ground, with metal cap attached to top, mkd. VTN RLS 6201, bears S. 80° 29' E., 3.488 chs. dist.</p> <p>38.472 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
--------------------------	---