449

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, TOWNSHIP 19 SOUTH, RANGE 60 EAST, MDM, NEVADA

CHAINS 40.463

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with a metal cap cemented in a concrete monument, 6 ins. diam., firmly set and exposed 2 ins. above the ground, with metal cap mkd. $\frac{1}{4}$ S5 S8 RLS 1919. This metal cap is accepted as a careful and faithful reestablishment of the position of the original corner. Remark the metal cap to read as follows:

BLM T19S R60E RLS S 5 1919 4 S 8

1990

N. 89° 52.2' W., beginning new measurement.

Over gently rolling land.

40.464

The cor. of secs. 5, 6, 7 and 8, monumented with and iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of T. 19 S., R. 60 E., executed under Group No. 357.

SURVEY OF THE SUBDIVISION OF SECTION 1, T. 19 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

From the ½ sec. cor. of secs. 1 and 12.

N. 0° 10.9' W., along the N-S center line of sec. 1.

Over nearly level land, through scattered shadscale and creosote brush.

30.60

South edge of Las Vegas Wash, bears WNW. and ESE.

41.234

The center $\frac{1}{4}$ sec. cor. of sec. 1, at intersection with the E-W center line of sec. 1, monumented with a metal cap cemented in a concrete monument, 6 ins. diam., firmly set flush with the surface of the ground, mkd. $C\frac{1}{4}$ S1 RLS 1624. This metal cap is accepted as a careful and faithful determination of the position of the corner. Remark the metal cap to read as follows: