

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
TOWNSHIP 14 SOUTH, RANGE 65 EAST, MDM, NEVADA

CHAINS	
	Over mountainous land, covered with creosote, chaparral and scattered cacti.
3.30	Ravine, drains NE.
9.70	Arrow Canyon Ravine, drains E.
40.835	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 7 only.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T14S R64E R65E   <math>\frac{1}{4}</math>   S 7</p> <p style="text-align: center;">1988</p>
53.60	Ridge, bears ENE. and WSW.
81.67	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to secs. 6 and 7 only.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T14S R64E R65E   S 6   S 7</p> <p style="text-align: center;">1988</p>
	N. $0^{\circ} 42'$ W., along the W. bdy. of sec. 6.
	Over mountainous land, covered with creosote, chaparral and scattered cacti.
22.20	Ridge, bears NNE. and SSW.
40.835	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 6 only.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T14S R64E R65E   <math>\frac{1}{4}</math>   S 6</p> <p style="text-align: center;">1988</p>