

DEPENDENT RESURVEY OF A PORTION OF
THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 63 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Independent Resurvey
Executed by J. W. Hardison and W. McConkie,
Public Land Surveyors, in 1938

From the standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented
with an iron post, 1 in. diam., firmly set showing 6
ins. above ground, with brass cap mkd. as described in
the field notes of the independent resurvey of the
Fourth Standard Parallel South, through a portion of
Range 63 East, executed under Group No. 237.

Remark the brass cap to read as follows:

SC
T16S R63E
 $\frac{1}{4}$ S 36

1987
1938

N. $89^{\circ} 59'$ E., along the S. bdy. of sec. 36.

Over nearly level land, covered with scattered
chaparral, creosote and cacti.

14.08

The N $\frac{1}{4}$ sec. cor. of sec. 7, T. 17 S., R. 64 E.,
monumented with an iron post, 1 in. diam., firmly set
showing 10 ins. above ground, with brass cap mkd. as
described in the field notes of the establishment of
the $\frac{1}{4}$ sec. cors. on N. bdy. of T. 17 S., R. 64 E.,
executed under Group No. 237. Remark the brass cap to
read as follows:

T16S R63E
 $\frac{1}{4}$ S 7
T17S R64E

1987
1938

23.78

Intersect the W. bdy. of sec. 31, T. 16 S., R. 64 E.

Point for the standard closing cor. of T. 16 S., R. 63
E. and T. 17 S., R. 64 E.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins.
diam., 24 ins. in the ground, with brass cap mkd.

SC |
T16S |
R63E | T16S
S 36 | R64E
CCS 7 | S 31
T17S |
R64E |

1987

Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the
stainless steel post.