

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 16 S., R. 63 E., MDM, NEVADA

CHAINS

From this same corner, the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 16 S., R. 63 E., executed under Group No. 317, bears S. $89^{\circ} 59' W.$
Remark the brass cap to read as follows:

T16S R63E

$$\frac{1}{4}$$
 S 35 | S 36

1941

1987

From this same corner, the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set showing 8 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of the E. bdy. of T. 16 S., R. 63 E., executed under Group No. 317, bears N. $89^{\circ} 59' E.$, 16.32 chs. dist. Hereafter, this corner will function as an amended monument.

Add the marks "AM 1987" to the brass cap.

From the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set showing 8 ins. above ground, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines of T. 16 S., R. 63 E., executed under Group No. 317. Remark the brass cap to read as follows:

T16S R63E

$$\frac{1}{4}$$
 S 24
 S 25

1941

1987

S. $89^{\circ} 59' E.$, bet. secs. 24 and 25.

Over gently rolling land, covered with scattered chaparral, creosote and cacti.

23.31 Intersect the W. bdy. of sec. 19, T. 16 S., R. 64 E.

Point for the closing cor. of secs. 24 and 25.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T16S
R63E R64E
S 24 | S 19
CCS 25 |

1987